

# UT | Split U-shaped cable grommet

for cables with connectors, tool-free assembly / up to IP54



The UT cable grommet is an U-shaped cable bushing and makes it possible to route single pre-connectorised cables as well as standard cables with a diameter range of 4 to 11 mm into enclosures.

The wall thickness of the enclosure can be from 1 to 4 mm.

The UT is a split grommet that can be mounted around the cable. The UT grommet is ideal for installation on the lower part of the enclosure.

After fitting the grommet with the cable, it is inserted into the recommended cut-out. The enclosure cover is then placed on the lower part.

**By screwing the cover tightly on the enclosure, pressure acts on the cable grommet and, depending on the properties of the enclosure, enables a sealing rate of up to IP54.**

IP54

HL3  
EN 45545-2

ECOLAB  
certified

UV  
ISO 4892-2A

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

## Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	
Operating temperature	-40 C° to 100 C°
Properties	UV-resistant, silicone free, halogen free
Mounting options	Snap-in
height	5 mm

## Advantages & benefits

- Allows the routing and sealing of cables that can vary in diameter up to 2 mm
- Simple, tool-free assembly
- Can be used for cable diameters from 4 to 11mm
- Protection class up to IP54 (if the grommet is selected correctly and depending on the enclosure properties)
- Cost-effective solution

## Product types & sizes


UTB bk



Part No.	<b>56100</b>
EAN	<b>4251269335464</b>
Package quantity	<b>10</b>
Length	<b>23,5 mm</b>
Width	<b>23 mm</b>
Height	<b>11 mm</b>


Mounting height	<b>5 mm</b>
For min. wall thickness	<b>1 mm</b>
For max. wall thickness	<b>4 mm</b>
Colour	<b>black</b>

UTB gy



Part No.	<b>56000</b>
EAN	<b>4251269335396</b>
Package quantity	<b>10</b>
Length	<b>23,5 mm</b>
Width	<b>23 mm</b>
Height	<b>11 mm</b>

Mounting height	<b>5 mm</b>
For min. wall thickness	<b>1 mm</b>
For max. wall thickness	<b>4 mm</b>
Colour	<b>grey (similar RAL 7035)</b>


**UT 4-6 bk**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Length  
Width  
Height

**56101**  
**4251269335471**  
**10**  
**1**  
**23,5 mm**  
**23 mm**  
**11 mm**

Mounting height  
For min. wall thickness  
For max. wall thickness  
Colour  
Clamping range

**5 mm**  
**1 mm**  
**4 mm**  
**black**  
**1 x 4 - 6 mm**


**UT 4-6 gy**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Length  
Width  
Height

**56001**  
**4251269335402**  
**10**  
**1**  
**23,5 mm**  
**23 mm**  
**11 mm**

Mounting height  
For min. wall thickness  
For max. wall thickness  
Colour  
Clamping range

**5 mm**  
**1 mm**  
**4 mm**  
**grey (similar RAL 7035)**  
**1 x 4 - 6 mm**


**UT 5-7 bk**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Length  
Width  
Height

**56102**  
**4251269335488**  
**10**  
**1**  
**23,5 mm**  
**23 mm**  
**11 mm**

Mounting height  
For min. wall thickness  
For max. wall thickness  
Colour  
Clamping range

**5 mm**  
**1 mm**  
**4 mm**  
**black**  
**1 x 5 - 7 mm**


**UT 5-7 gy**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Length  
Width  
Height

**56002**  
**4251269335419**  
**10**  
**1**  
**23,5 mm**  
**23 mm**  
**11 mm**

Mounting height  
For min. wall thickness  
For max. wall thickness  
Colour  
Clamping range

**5 mm**  
**1 mm**  
**4 mm**  
**grey (similar RAL 7035)**  
**1 x 5 - 7 mm**


**UT 6-8 bk**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Length  
Width  
Height

**56103**  
**4251269335495**  
**10**  
**1**  
**23,5 mm**  
**23 mm**  
**11 mm**

Mounting height  
For min. wall thickness  
For max. wall thickness  
Colour  
Clamping range

**5 mm**  
**1 mm**  
**4 mm**  
**black**  
**1 x 6 - 8 mm**


**UT 6-8 gy**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Length  
Width  
Height

**56003**  
**4251269335426**  
**10**  
**1**  
**23,5 mm**  
**23 mm**  
**11 mm**


Mounting height  
For min. wall thickness  
For max. wall thickness  
Colour  
Clamping range

**5 mm**  
**1 mm**  
**4 mm**  
**grey (similar RAL 7035)**  
**1 x 6 - 8 mm**

**UT 7-9 bk**


Part No. **56104**  
 EAN **4251269335501**  
 Package quantity **10**  
 For max. no. of cables **1**  
 Length **23,5 mm**  
 Width **23 mm**  
 Height **11 mm**

Mounting height **5 mm**  
 For min. wall thickness **1 mm**  
 For max. wall thickness **4 mm**  
 Colour **black**  
 Clamping range **1 x 7 - 9 mm**

**UT 7-9 gy**


Part No. **56004**  
 EAN **4251269335433**  
 Package quantity **10**  
 For max. no. of cables **1**  
 Length **23,5 mm**  
 Width **23 mm**  
 Height **11 mm**

Mounting height **5 mm**  
 For min. wall thickness **1 mm**  
 For max. wall thickness **4 mm**  
 Colour **grey (similar RAL 7035)**  
 Clamping range **1 x 7 - 9 mm**

**UT 8-10 bk**


Part No. **56105**  
 EAN **4251269335518**  
 Package quantity **10**  
 For max. no. of cables **1**  
 Length **23,5 mm**  
 Width **23 mm**  
 Height **11 mm**

Mounting height **5 mm**  
 For min. wall thickness **1 mm**  
 For max. wall thickness **4 mm**  
 Colour **black**  
 Clamping range **1 x 8 - 10 mm**

**UT 8-10 gy**


Part No. **56005**  
 EAN **4251269335440**  
 Package quantity **10**  
 For max. no. of cables **1**  
 Length **23,5 mm**  
 Width **23 mm**  
 Height **11 mm**

Mounting height **5 mm**  
 For min. wall thickness **1 mm**  
 For max. wall thickness **4 mm**  
 Colour **grey (similar RAL 7035)**  
 Clamping range **1 x 8 - 10 mm**

**UT 9-11 bk**

Part No. **56106**  
 EAN **4251269335525**  
 Package quantity **10**  
 For max. no. of cables **1**  
 Length **23,5 mm**  
 Width **23 mm**  
 Height **11 mm**

Mounting height **5 mm**  
 For min. wall thickness **1 mm**  
 For max. wall thickness **4 mm**  
 Colour **black**  
 Clamping range **1 x 9 - 11 mm**

**UT 9-11 gy**

Part No. **56006**  
 EAN **4251269335457**  
 Package quantity **10**  
 For max. no. of cables **1**  
 Length **23,5 mm**  
 Width **23 mm**  
 Height **11 mm**

Mounting height **5 mm**  
 For min. wall thickness **1 mm**  
 For max. wall thickness **4 mm**  
 Colour **grey (similar RAL 7035)**  
 Clamping range **1 x 9 - 11 mm**

