KEL-FA | Split multi cable entry frames

for cables with connectors, tool-free assembly / IP54 / UL Type 12



.**71**2'115

The KEL-FA range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising KT series grommets. After populating the entry frame with grommets and cables, the cover is put on and the two clamping levers are locked with the lower part by pressing them down. The twist-proof construction of the KEL-FA enables intuitive assembly. Routing and sealing with IP54 / UL Type 12 for cable diameters from 1 to 35 mm.

The KEL-FA frames match exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. These KEL-FA frames can either be screw mounted or simply snapped into the $\underline{\text{KEL-SNAP frame}}$.

Specifications

123

IP54

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	UV-resistant, silicone free, anti- corrosive, halogen free
Mounting options	Screw type mounting,Snap-in with KEL-SNAP

Advantages & Benefits

Integrated sealing

RoHS

- Quick assembly without tools
- Strain relief according to EN 62444 (when using KT single hole grommets)
- Very high cable density with multi-hole grommets
- High flexibility with multi-range grommets and the IMAS-CONNECT™ system
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Wide variety

Product types & Sizes

KEL-FA 24 10							
6						Hor	

 Part No.
 55241

 EAN
 4251269324796

 Package quantity
 10

 For max. no. of cables
 40

 Max. cable diameter
 15 mm

 Length
 147 mm

 Width
 62 mm

Height 22 mm

Mounting height 22 mm


Cut-out size 112 × 36 mm

No. of screw holes 4

Diam. of screw holes 6 mm

Suitable for grommets 10 x KT small

KEL-FA 24|7



Part No. 55247
EAN 4251269324802
Package quantity 10
For max. no. of cables 25
Max. cable diameter 35 mm
Length 147 mm
Width 62 mm

Height 22 mm

Mounting height 22 mm

Cut-out size 112 × 36 mm

No. of screw holes 4

Diam. of screw holes 6 mm

Suitable for grommets 6 x KT small 1 x KT large

KEL-FA 24|4



Part No. EAN Package quantity For max. no. of cables

Length Width

Max. cable diameter 35 mm

55244

4251269324819 10

147 mm 62 mm

Height


Mounting height Cut-out size No. of screw holes

Diam. of screw holes Suitable for grommets 22 mm 22 mm

112 × 36 mm

6 mm 2 x KT small 2 x KT large

KEL-FA 16|8



Part No. EAN

Package quantity For max. no. of cables Max. cable diameter

Length Width

55168

4251269324826

Height


Mounting height Cut-out size

No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm

86 × 36 mm

6 mm 8 x KT small

KEL-FA 16|5



Part No. EAN

Package quantity For max. no. of cables Max. cable diameter

Lenath Width

55165

4251269324833

Height


Mounting height Cut-out size No. of screw holes

Diam. of screw holes Suitable for grommets 22 mm 22 mm

86 × 36 mm

6 mm 4 x KT small 1 x KT large

KEL-FA 16|2



Part No.

EAN Package quantity For max. no. of cables Max. cable diameter

Length Width

55162

4251269324840


Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm

86 × 36 mm 4

6 mm 2 x KT large

KEL-FA 10|6



Part No. FAN

Package quantity For max. no. of cables Max. cable diameter

Length Width

55216

4251269324857


Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm

22 mm 65 × 36 mm

> 6 mm 6 x KT small

KEL-FA 10|3



Part No.

Package quantity For max. no. of cables Max. cable diameter

Length Width

55212

4251269324864

10 35 mm 100 mm 62 mm

Height

Mounting height Cut-out size No. of screw holes

Diam. of screw holes Suitable for grommets 22 mm

22 mm 65 × 36 mm

6 mm

2 x KT small 1 x KT large



smart cable management